



CHEMPOL 4155

Automatic Transmission Fluid Additive

PRODUCT DESCRIPTION

CHEMPOL 4155 is automatic transmission fluid (ATF) additive that is formulated to meet the stringent transmission fluid requirements of Ford and General Motors, and is suitable for use in all Ford and GM vehicles of model years 2005 and earlier and all Allison C4 applications, and any other application calling for use of DIIH/M quality ATF. Use at 8.2% wt. (7.66% vol.) when combined with a suitable Group II base oil

DOSAGE RECOMMENDED (WT%)

Performance level	Dosage
DEXRON III H/M, ALLISON C4	8.2

PRODUCT CHARACTERISTICS

Item	Index	Typical Value	Test Method
Appearance	Dark Brown Viscous Liquid	Dark Brown Viscous Liquid	Visual
Kinematic Viscosity (100°C) mm ² /s	250-290	270	ASTM D445
Density (15°C), kg/m ³	900-950	912	ASTM D4052
Flash Point (COC), °C	≥140	<180	ASTM D92
B Content, ppm	630-700	670	ASTM D5185
N Content, m%	0.93-1.03	0.98	ASTM D5291
P Content, m%	0.16-0.20	0.18	ASTM D5185

PACKING, STORAGE AND TRANSPORTATION

Please refer MSDS of this product when storing, shipping, handling and using this product. It is nonflammable, non-explosive and non-corrosive. The highest storage temperature shall not exceed 75°C. For long term storage, the highest temperature shall not more than 45°C. For product details of safety, health and environmental precautions, please refer to the MSDS of this product.