



CHEMPOL 4373A

Automatic Transmission Fluid Additive

PRODUCT DESCRIPTION

CHEMPOL 4373A multi-vehicle automatic transmission fluid (ATF) additive package is designed to formulate ATF for DEXRON®-VI, MERCON® LV, JASO 1 ALV applications with Group III base stocks.

FEAUTRES

- ❖ Helps improve fuel economy
- ❖ Provides consistent shift performance for the life of the vehicle
- ❖ Extends transmission fluid life and prevents fluid breakdown at higher operating temperatures
- ❖ Reduces sludge and varnish build-up
- ❖ Protects transmission gears and allows them to operate smoothly
- ❖ Flows well for cold start-up
- ❖ Field tested performance

DOSAGE RECOMMENDED (WT%)

Performance level	Dosage
DEXRON®-VI, MERCON® LV, JASO 1 ALV	11

PRODUCT CHARACTERISTICS

Item	Index	Typical Value	Test Method
Appearance	Dark Brown Viscous Liquid	Dark Brown Viscous Liquid	Visual
Kinematic Viscosity (100°C) mm ² /s	60-80	70	ASTM D445
Density (15°C), kg/m ³	900-950	920	ASTM D4052
Flash Point (COC), °C	≥140	<180	ASTM D92
B Content, ppm	640-710	680	ASTM D5185
N Content, m%	1.12-1.37	1.25	ASTM D5291
P Content, m%	0.13-0.17	0.15	ASTM D5185
S Content, m%	1.37-1.68	1.53	ASTM D4294

PACKING, STORAGE AND TRANSPORTATION

Please refer MSDS of this product when storing, shipping, handling and using this product. It is nonflammable, non-explosive and non-corrosive. The highest storage temperature shall not exceed 75°C. For long term storage, the highest temperature shall not more than 45°C. For product details of safety, health and environmental precautions, please refer to the MSDS of this product.