



CHEMPOL 7182

Diesel & Gasoline Engine Oil
Additive

PRODUCT DESCRIPTION

CHEMPOL 7182 additive is an economic diesel & gasoline engine oil package developed to meet a range of specific market requirements. This additive can be used to blend API CF-4, CF-4/SJ & CF/SF performance oils.

DOSAGE RECOMMENDED (WT%)

The recommended dosage of **CHEMPOL 7182** is **9.0%** by wt.

- API CF-4
- API CF-4/SJ
- API CF/SF

TYPICAL CHARACTERISTICS

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Dark color, Viscous Liquid	Visual
Specific Gravity @ 15.6°C g/ml	0.99	ASTM D4052
Flash Point (COC), °C	150	ASTM D92
Kinematic Viscosity @ 100°C, cSt	95-150	ASTM D445
Calcium, wt%	2.90	ASTM D5185
Zinc, wt%	1.33	ASTM D5185
Phosphorus, wt%	1.20	ASTM D5185
Total Base Number, mg KOH/g	92	ASTM D2896

PACKING, STORAGE AND TRANSPORTATION

Please observe the US DOT standard and the MSDS of this product when storing, shipping, handling and using this product. It is nonflammable, non-explosive and non-corrosive. The highest storage temperature shall not exceed 75°C. For long term storage, the highest temperature shall not more than 45°C. For product details of safety, health and environmental precautions, please refer to the MSDS of this product.