



CHEMPOL 7601

Tractor Oil Additive

PRODUCT DESCRIPTION

CHEMPOL 7601 additive is a rationalized additive system for the formulation of STOUS meeting the requirements of all tractors.

DOSAGE RECOMMENDED (WT%)

The recommended dosage for CHEMPOL 7601 additive is 13.0 wt% to meet all of the latest tractor requirements. At 11.5 wt%, CHEMPOL 7601 additive can be used to provide an economic STOUS meeting the basic needs of the market.

FEATURES

- ❖ Wear and Friction control suitable for all transmissions, including power shift transmissions covered by Ford 134-D
- ❖ Diesel engine performance up to and including API CF-4
- ❖ Gear protection for hypoid axles, which have completed break-in.

TYPICAL CHARACTERISTICS

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Dark color, Viscous Liquid	Visual
Specific Gravity @ 15.6°C g/ml	1.0	ASTM D4052
Flash Point (COC), °C	≥180	ASTM D92
Kinematic Viscosity @ 100°C, cSt	Report	ASTM D445
Calcium, wt%	2.60-2.88	ASTM D5185
Zinc, wt%	1.05-1.15	ASTM D5185
Phosphorus, wt%	0.92-1.02	ASTM D5185
Total Base Number, mg KOH/g	80-90	ASTM D2896

PACKING, STORAGE AND TRANSPORTATION

Please observe the US DOT standard and the MSDS of this product when storing, shipping, handling and using this product. It is nonflammable, non-explosive and non-corrosive. The highest storage temperature shall not exceed 75°C. For long term storage, the highest temperature shall not more than 45°C. For product details of safety, health and environmental precautions, please refer to the MSDS of this product.